

GRAFFITI MAGIC LIMITED

Units 15 and 6, Riverside Industrial Estate
West Hythe Road, West Hythe Road, Kent CT 21 4NB England
Tel: +44 (0)1303 260900 Fax: +44 (0) 1303 263700



WATER BASED PRIMER ADHESION PROMOTER FOR NON-POROUS SURFACES

Description: A universal with water dilutable adhesive primer with light corrosion inhibition properties.

Most important properties:

- ◆ prevents rust
- ◆ scratch-, and wear proof
- ◆ insulation layer on Medium Density Fibreboard (MDF)
- ◆ excellent adhesion and easy to apply

Applications:

- ◆ on glass, tiles, wood, several synthetic materials, various metals and powder coated undergrounds
- ◆ if in doubt first apply to a test surface

Product information

- binder* ◆ acrylate dispersion
- glow grade* ◆ matt
- density* ◆ 1,35 kg/litre
- theoretical efficiency* ◆ 10 - 15 m² per litre at 75 µm wet layer thickness
- tenability* ◆ approx. 12 month in unused packing
- conservable* ◆ keep cool and away from frost

Processing data:

- processing* ◆ by brush, roller and spray
- drying at 20°C* ◆ after out 1 hour
- processing conditions* ◆ after approx. 1-2 hours with several paint systems and water soluble and solvent containing products repaint able depending on the relative humidity
- dilution* ◆ maximal 10% with water
- cleaning materials* ◆ immediately with luke warm water

Delivery:

- packaging* ◆ 5 litres
- colour* ◆ transparent

Systems:

- pre-treatment* ◆ remove inferior paint layers
- ◆ underground must be dry, clean and greaseproof
- ◆ sandpaper surface and degrease with water based cleaner.
- ◆ galvanized surfaces sandpaper mechanically and degrease with thinner, immediately apply Adhesion Promoter.
- ◆ Adhesion Promoter in not too thin layers due to the fact this can negatively influence the primer

Safety data:

See the safety data sheets